



Trend Synergy® Aluminium

Widestyle Double Hung

Features & Benefits

Size Range

Ordering Details

Installation

Cross Sectional Views




Features & Benefits

Synergy® Widestyle Double Hung

- 1 Energy Efficiency Options To reduce energy consumption, Thermashield® systems are available in various WERS ratings and glazing styles.
- 2 Acoustic Options SoundMizer® acoustic solutions are available for double hung windows. SoundMizer® acoustic solutions can reduce aircraft, highway traffic, railway and other annoying noise problems. For information or technical details contact Trend®.
- 3 Lock hardware
 Black is supplied as standard.
 Optional colours are anodic
 natural matt, stone beige, pearl
 white and satin chrome.
- 4 Key locks
 All Trend® Standard Double
 Hung Windows are available
 with standard key lock that
 can be keyed to match other
 Trend® aluminium windows. Vent
 locks are available for Trend®
 Double Hung Windows.
- 5 Interlocking Meeting Rails
 The interlocking meeting rails
 on the sashes combine together
 when closed to improve the overall
 weather performance strength.
 The sashes by-pass to facilitate
 easy internal glass cleaning.

- 6 Weather sealed for full protection All sashes are fitted with weatherpile seals to keep the dust and water where they belong, on the outside.
- 7 Complementary Accessories
 - 180° non-load bearing couplers, two types available for added mullion strength when required.
 - 135° & 90° non-loadbearing corner couplers to suit bay and kitchen windows.
 - 100mm aluminium architraves for replacement window installations.
 - Adjustable aluminium storm mould.
 - Aluminium 180° and 90° mullion covers to hide load-bearing posts.
- 8 Options
 Colonial Bar and Federation
 Bar Layouts are available
 Ovolo bar layout available
 Horns are available
 Double glazing is available
 Easy to fit flyscreens
 Colour matched finger lifts
 Wide range of powdercoat finishes
 For bushfire areas this product
 rates up to BAL-29

*Note: Double glazing is not available with ovolo glazing bar







Size Range

Synergy® Widestyle Double Hung

	2.5	3	3.5	070	5	6	1570	6.5	7.5
ate o	670	790 768	910 888	970 948	1270 1248	1510 1488	1570 1548	1630 1608	1870 1848
OCK SETTING	610	730	850	910	1210	1450	1510	1570	1810
Sin Sin The	7								
917 895 857	SWD0806	SWD0807	SWD0808	SWD0809	SWD0812	SWD0814	SWD0815	SWD0816	SWD0818
938	SWD0906	SWD0907	SWD0908	SWD0909	SWD0912	SWD0914	SWD0915	SWD0916	SWD0918
1090	SWD1006	SWD1007	SWD1008	SWD1009	SWD1012	SWD1014	SWD1015	SWD1016	SWD1018
1260 1238 1200	SWD1206	SWD1207	SWD1208	SWD1209	SWD1212	SWD1214	SWD1215	SWD1216	SWD1218
1430 1408 1370									
1517 1495 1457	SWD1306	SWD1307	SWD1308	SWD1309	SWD1312	SWD1314	SWD1315	SWD1316	SWD1318
27 27 7	SWD1406	SWD1407	SWD1408	SWD1409	SWD1412	SWD1414	SWD1415	SWD1416	SWD1418
1560 1538 1500					. Z			<u> </u>	
0 8 0	SWD1506	SWD1507	SWD1508	SWD1509	SWD1512	SWD1514	SWD1515	SWD1516	SWD1518
1860 1838 1800	SWD1806	SWD1807	SWD1808	SWD1809	SWD1812	SWD1814	SWD1815	SWD1816	SWD1818
207:	0/21			<u> </u>		A	A		X
		SWD2007T	SWD2008T	SWD2009T	SWD2012T	SWD2014T	SWD2015T	SWD2016T	SWD2018T
2160 2138 2100	000	SWD2107T	SWD2108T	SWD2109T	SWD2112T	SWD2114T	SWD2115T	SWD2116T	SWD2118T
				in full heigh					
	THESE WILL	10W2 0120	avanable	iii ioii neigr	11				



All windows and doors are designed to 700pa velocity and 150pa water rating. For higher ratings consult Trend® Windows & Doors


Please note that drawings are not to scale

Synergy® Widestyle Double Hung | AWD | Mk-7 | 4 July 2013



Size Range

Synergy® Widestyle Double Hung





All windows and doors are designed to 700pa velocity and 150pa water rating. For higher ratings consult Trend® Windows & Doors



Ordering Details

Synergy® Widestyle Double Hung

All windows are illustrated as viewed from outside. Codes shown are for plain windows.

Manufactured from 64mm aluminium extrusion. The first two numbers of code indicate approximate height, the last two numbers indicate approximate width.

Sash Style Options:

Standard option, eg window code AWD0906

O indicates Ovolo D/Hung sash with Ovolo Glazing Bar, eg window code AOWD0906CL

T indicates Thermashield® double glazed sash style, eg window code ATWD0906

*Thermashield Double glazing is not available with the ovolo bar and glue on bar configurations

Note: Frames over 1800mm high with full height operating sashes, the maximum sash width is 720mm

Bar Options:

CL indicates Colonial Bar, eg window code AWD0906CL FED indicates Federation Bar, eg window code AWD0906FED

Configuration Options:

DF indicates Double Hung/Fixed FD indicates Fixed/Double Hung DD indicates Double Hung/Double Hung DFD indicates Double Hung/Fixed/Double Hung DDD indicates Double Hung/Double Hung/Double Hung/Touble Hung/Touble Hung/Touble Hung F indicates Fixed T after the size indicates a Transom

This product rates up to BAL-29

Hardware Colour Options

Black hardware is supplied as standard

Optional colours are Anodic Natural Matt, Stone Beige, Pearl White & Satin Chrome


Vent lock option is available





Installation

Synergy® Widestyle Double Hung | Building In Detail | Brick Veneer - 230mm wall








Installation

Synergy® Widestyle Double Hung | Building In Detail | Double Brick - 280mm wall








Installation


Synergy® Widestyle Double Hung | Building In Detail | Aluminium Cladding on Studs








Trend® Widestyle Double Hung | Single Lite








Trend® Widestyle Double Hung | Two Lite with Lowlite





Trend® Widestyle Double Hung | Two Lite with Lowlite







Trend® Widestyle Double Hung | **Double Glazed**

WINDOWS

